

Product specifications

Panel characteristics

Support bar (1)	SPCC, 1.5mm thickness with 5 to 8um Nickel plated	
Rear panel (2)	SPCC, 1.5mm thickness, with a nickel plated layer of 5 to 8µm, and black (RAL 9005) finish	
Frame (3)	ABS-HB	
Identification (4)	Paper and frame PC, UL 94V-2	
Ground cable (5)	18 AWG wire, with green/yellow stripes, 40cm in length	
Number of ports	24	48
Effective U space	0.5U	1U
Mounting type	Rack mountable	
Insertion force	30N max (IEC 60603-7-5)	
Retention strength	7.7 Kgs between jack and plug	
Operating temperature	-10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA-568-C.2)	

Dimensions

Height (in/mm)	0.875in / 22.2mm	1.75in / 44.4mm
External width (in/mm)	19in / 482.6mm	
Depth (in/mm)	0.50in / 12.8mm	
Depth with support bar (in/mm)	5.91in / 150mm	
Includes	4 M5 x L12mm screw set and plastic ties	

Certifications and Standards

International standards	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801	
-------------------------	-------------------------------------	--

Miscellaneous

MPN	PCGPSPMOHU24HDBK	PCGPSSMO1U48HDBK
UPC	798302033825	798302033849
Labeling	NEXXT SOLUTIONS	NEXXT SOLUTIONS SHIELDED HD
Packaging	Carton box	
Quantity per pack	One unit	
Cuft	2.82 per 15units	1.13 per 6units
Warranty	5-year limited warranty**	

SPCC: Commercial grade, cold rolled steel sheets

