

Our 4-post 19-inch standard steel racks are designed for the mounting of equipment for cable installations, especially where easy access to cables is necessary. These racks provide more space to accommodate networking equipment and offer improved cable management. Built to EIA rack standards, it allows the quick attachment of equipment, such as large modular network or voice switches, routers and other network devices in communications. Available in 30 and 45 units of rack.



PCRORSKD30U4PBK  
PCRORSKD45U4PBK



- Steel structure with modular and removable components.
- Available with 4-post that accommodate EIA industry-standard 19-inch panels.
- Follows ANSI/TIA/EIA-568 C.2 manufacturing standards and meets ANSI/EIA RS-310-C, D, E, F criteria.
- One layer of electrostatic coating protects it against humidity, rust, scratches, peeling, strong acid and alkaline erosion.
- Black epoxy-polyester hybrid powder coating.
- For indoor use only, in environmentally controlled areas, may not be used outdoors, in industrial or harsh environments or in plenum spaces.
- Other accessories available to meet any mounting need.
- Use with shelves or rails to support large, heavy computer and data storage equipment.



**Product specifications**

Open rack characteristics		
Color	Black epoxy-polyester hybrid powder paint (RAL 9005)	
Rack size	4ft	7ft
Effective U space	30U	45U
Mounting type	Floor mounted	
Pole quantity	4	
Hole size/type	Square holes	
Material (cover)	SPCC, 2.0mm thickness	
Material (frame)	SPCC, 2.0mm thickness	
Material (base)	SPCC, 6.0mm thickness	

Dimensions		
Height	60.08in	86.33in
External width	21.65in	
Depth	23.62in	
Bottom depth	35.43in	
Load capacity	Can hold up to 2,215lb	

Includes	2	Front and rear top mounting rail	2
	4	Horizontal mounting rail	4
	2	Lateral support bar	4
	4	Vertical frame post	4
	2	Front and rear bottom base M8xL20 hex head cap screw and M8 flat washer, spring washer and flange nut set	2
	12	M6xL12 philips screw and M6 flange nut set	12
	24	M6xL12 screw, plastic washer and caged nut set	36
	40	Expansion anchor bolts	40
	4	User manual	4
	1		1

Certifications and standards	
International standards	UL 60950 or UL 60950-1, or UL 60950-21 as appropriate ISSO/IEC 11801, ANSI/TIA/EIA 568.C.2 ANSI/EIA RS-310-C, D, E, F
UL certificate	UR E480900

Miscellaneous		
MPN	PCRORSKD30U4PBK	PCRORSKD45U4PBK
UPC	798302034716	798302034730
Labeling	NEXXT SOLUTIONS	
Packaging	Carton box	
Cuft	2.68	3.37
Warranty	5-year limited warranty**	

SPCC: Commercial grade, cold rolled steel sheets

